

HUNTONIT

FDV - 056

| | |
|-----------------|--|
| Product: | Huntonit Symfoni/Brush Painted Panel |
| Format: | Board |
| | 11 x 142/125 x 2420/2400 and 3020/3000 mm |
| | 11 x 200/180 x 2420/2400 mm |

| | |
|---------------------------------|--|
| Areas of Use Mounting | Can be used on all ceilings in residential areas, including wet rooms. A normal 2.4 m ceiling height and suitable ventilation are required for wet rooms. Mounted on electrical lath, or directly across dry joists or lath. Then with the end joints on the joist/lath. |
| Ties | Ties with a >10 mm back and corresponding capacity. |
| Metal/wood screw | BK 25. Christiania Spigerverk, or equivalent. |
| In concrete | Fischer nail plug N5X39Z or equivalent. |
| Distance of fastening points | Mounted lengthwise: cc 15–20 cm. Mounted transversely: 2 per intersection, and 3. at the end joint. |

Dealer

| | |
|-----------|---|
| Name | Huntonit AS |
| Address | PO Box 21, 4701 Vennesla, Norway |
| Telephone | 381 37100 |
| Fax | 381 37101 |
| Website | http://www.byggma.no |
| E-mail | byggma@byggma.no |

Product Description

| | |
|-----------------------|---|
| Designation | Huntonit Panel Board with Symphony/Brush Painted surface |
| Paint type | Acrylic paint. Y1 group 00 Manufacturer: Steen Hansen, maling AS. Bergen, Norway |
| Color/glossiness | Various colors Glossiness 20 |
| Maintenance painting | Overpainting. High quality acrylic interior paint |
| Maintenance frequency | As needed for wear and tear, depending on use |
| Cleaning | Washable with damp cloth. Do not steam clean |
| Degassing | No harmful emissions to the indoor environment. NBI (571.04) |

Notes

| | |
|-------------------------------|---|
| Indoor storage | Store in dry conditions. Acclimate/temper in the packaging |
| Wallpaper paste | When wallpapering, any wallpaper paste that gets on the ceiling panels must be washed off immediately. Wallpaper paste acts as a slow-acting paint remover. |
| Shaping | Cut with a saw. Suction on saw is recommended |
| Acclimating | Do not remove from packaging prior to mounting Stabilize to room temperature. |
| Construction site environment | All masonry and sanding work must be completed before the panels are removed from the packaging. |
| Fire classification | D-s2, d0 in accordance with NS-EN 13501-1 |
| NAAF | Recommended by the Norwegian Asthma and Allergy Association |
| Approval | TG 2038 (from SINTEF Certification) |

Modified: 03/17/2015

Replaces: 01/17/2023